

Product Environmental Profile

DataCom Plastic Workstation Wall Plates



PRODUCTS CONCERNED

The environmental data is representative of the following product families (includes single gang, double gang, and multi-ports).

- | | |
|---|--|
| TracJack® Faceplates (OR-403*) | 106-Type TracJack Frames (OR-408*) |
| Series II® Faceplates (OR-403*) | Stylistics TracJack Frames (OR-419*) |
| High Density Jack Faceplates (OR-403HDJ*) | |
| TechChoice® Faceplates (OR-KSFP*) | 106-Type Cover Plates (OR-403*) |
| | Stylistics Cover Plates (OR-403*) |
| TracJack Furniture Plates (OR-403*, OR-407*, OR-421*) | |
| Series II Furniture Plates (OR-403*) | 106-Type TechChoice Frames (OR-KS106S*) |
| High Density Jack Furniture Plates (OR-421HDJ*) | Stylistics TechChoice Frames (OR-KSDS*) |
| Series II Bezel for HDJ (10 pack) (OR-S22HDJ10*) | Stylistics High Density Jack Frames (OR-419HDJ*) |
| Series II Bezel for TechChoice (10 pack) (OR-KSS210*) | |
| TracJack Adapter Bezel for HDJ (20 pack) (OR-HDJTJA20*) | |



CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EC and does not contain, as far as we know, any substance on the candidate list from June 2015 for authorization of the REACH regulation (EC) no. 1907/2006 with a concentration above 0.1% w/w.

Total weight of Reference Product (with unit packaging)	58.6 g				
Plastics as % of weight		Metals as % of weight		Others as % of weight	
Product					
PC/ABS	60.3%	Steel	13.0%	Paper	0.4%
		Nickel	<0.1%		
Packaging					
PE (low density)	8.5%			Cardboard	17.8%
Total plastics	68.8%	Total metals	13.0%	Total others	18.2%

Estimated recycled material content: 18% of weight.

Note: The products covered within the PEP use different plastic wall plates compared to the Reference Product, which has a PC/ABS wall plate. The alternative plastics used are the following: ABS, PC, and Nylon 6. This does not have a significant impact on the recycled material content so 10% is used to represent all plate material types. The environmental impact of the various types of plastics used, compared to the impacts of the Reference Product, is reflected in the extrapolation rules at the end of the PEP.



MANUFACTURING

The Reference Product comes from a site that observes the applicable legislation for industrial sites.



DISTRIBUTION

Products are distributed from logistics centers located to optimize transport efficiency using EPA SmartWay® certified carriers to reduce greenhouse gases emissions. Information on the distance of distribution is not available so the PCR hypothesis for "Intracontinental transport", 2175 miles (3500 km) by heavy truck, was used. This represents transportation of the Reference Product from our warehouse to the local point of distribution in the North American market.

Product Environmental Profile

DataCom Plastic Workstation Wall Plates



INSTALLATION

Only standard tools are needed for installation of the product. No electricity is required for installing the Reference Product.



USE

Servicing and maintenance:

Under normal conditions of use, this type of product requires no servicing or maintenance.

Consumable:

No consumables are necessary to use this type of product.



END OF LIFE

• **Hazardous waste* contained in the product:** no hazardous waste
 (*) Hazardous waste as defined by European Commission decision 2000/532/EC.

• **Recycling rate:**

Calculated using the method described in the IEC/TR 62635 technical report, the recyclability rate of the Reference Product without packaging is estimated as 96%. This value is based on data collected from a technological channel using industrial procedures. It does not pre-validate the effective use of this channel for end-of-life electrical and electronic products.

Separated into:	(% mass of Reference Product excluding packaging)
- plastic materials:	78%
- metal materials:	18%
- other materials:	1%

Recycling rate of packaging (all types of materials): 68%



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use, and end of life. It is representative of products marketed and used in North America.

The following modelling elements were taken into account:

Manufacturing	Packaging taken into account up to third level packaging. As required by the PEP ecopassport program, all transport for the manufacturing of the Reference Product, including materials and components, has been taken into account. The waste generated during manufacturing phase has been taken into account.
Distribution	Transport between the last distribution center and an average delivery to the sales area. The default scenario modelled maximizes the environmental impact using the PCR hypothesis for "Intracontinental transport": 2175 miles (3500 km) by heavy truck.
Installation	The end of life of the packaging (58.6 g) is taken into account at this phase. Transport of packaging to end of life treatment.
Use	<ul style="list-style-type: none"> • Under normal conditions of use, this type of product requires no servicing or maintenance. • No consumables are necessary to use this type of product. • Product category: enclosure • Use scenario: no energy consumption during the 20 year working life. This modelling duration does not constitute a minimum durability requirement. • Energy model: Electricity(US) - 2009
End of life	The default end of life scenario modelled maximizes the environmental impact using the PCR hypothesis for "Local transport": 621 miles (1000 km) by heavy truck and landfilling.
Software used	EIME V5 and its database "CODDE-2015-04" and the indicators defined in the PCR ed 3 in alignment with the EN15804 standard

Product Environmental Profile


DataCom Plastic Workstation Wall Plates



ENVIRONMENTAL IMPACTS (continued)

	Total for Life cycle		Raw material and manufacturing		Distribution		Installation		Use		End of life	
	Value	Unit	Value	%	Value	%	Value	%	Value	%	Value	%
Global warming (GW)	4.33E-01	kg CO ₂ eq.	4.17E-01	96%	1.02E-02	2%	1.25E-03	< 1%	0.00E+00	0%	4.76E-03	1%
Ozone depletion (OD)	1.96E-08	kg CFC-11 eq.	1.94E-08	99%	2.07E-11	< 1%	1.97E-11	< 1%	0.00E+00	0%	1.12E-10	< 1%
Acidification of soil and water (A)	8.42E-04	kg SO ₂ eq.	7.73E-04	92%	4.59E-05	5%	5.46E-06	< 1%	0.00E+00	0%	1.83E-05	2%
Water eutrophication (WE)	2.02E-04	kg PO ₄ ³⁻ eq.	1.63E-04	81%	1.05E-05	5%	6.03E-06	3%	0.00E+00	0%	2.20E-05	11%
Photochemical ozone creation (POCP)	9.06E-05	kg C ₂ H ₄ eq.	8.55E-05	94%	3.26E-06	4%	4.02E-07	< 1%	0.00E+00	0%	1.42E-06	2%
Depletion of abiotic resources - elements (ADPe)	7.75E-08	kg Sb eq.	7.68E-08	99%	4.08E-10	< 1%	6.68E-11	< 1%	0.00E+00	0%	2.95E-10	< 1%
Total use of primary energy (PE)	9.41E+00	MJ	9.17E+00	97%	1.44E-01	2%	1.85E-02	< 1%	0.00E+00	0%	7.25E-02	< 1%
Net use of fresh water (FW)	1.64E-03	m ³	1.64E-03	100%	9.14E-07	< 1%	7.31E-07	< 1%	0.00E+00	0%	3.88E-06	< 1%
Depletion of abiotic resources - fossil fuels (ADPf)	6.14E+00	MJ	5.91E+00	96%	1.43E-01	2%	1.76E-02	< 1%	0.00E+00	0%	6.73E-02	1%
Water pollution (WP)	1.75E+02	m ³	1.72E+02	99%	1.68E+00	< 1%	1.68E-01	< 1%	0.00E+00	0%	5.52E-01	< 1%
Air pollution (AP)	3.36E+01	m ³	3.25E+01	97%	4.18E-01	1%	1.53E-01	< 1%	0.00E+00	0%	5.34E-01	2%

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website. The environmental impacts of the Reference Product are representative of the products covered by the PEP, which therefore constitute a homogeneous environmental family.



The environmental impact of the Reference Product occurs predominantly during the manufacturing phase.

Product Environmental Profile

DataCom Plastic Workstation Wall Plates



ENVIRONMENTAL IMPACTS (continued)

For products other than the Reference Product, the environmental impacts for Manufacturing and Distribution are proportional to the mass of the Reference Product. The impacts for Manufacturing of products with various wall plate material types should then be multiplied by the corresponding values for the applicable wall plate material type in the table below. Impacts for Installation are the same as the Reference Product. Impacts for End of Life are proportional to the mass of the Reference Product (without packaging).

Wall Plate Material Type	Manufacturing
PC/ABS wall plate	1.0
ABS wall plate	GW: 0.7 WP: 0.3 all else: 1.0
PC wall plate	WP: 1.3 all else: 1.0
Nylon 6 wall plate	ADPe: 0.5 WE: 1.8 WP: 0.3 all else: 1.2
PC/ABS wall plate with brass insert	ADPe: 7.36 all else: 0.4

Registration number: LGRP-00058-V01.02-EN	Drafting rules: "PCR-ed3-EN-2015 04" Supplemented by "PSR-0005-ed2-EN-2016 03 29"
Verifier's accreditation number: VH02	Information and reference documents: www.pep-ecopassport.org
Date of issue: 09-2016	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025:2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR Review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN).	
The elements of the present PEP cannot be compared with elements from another program.	
Document in compliance with ISO 14025:2010: "Environmental labels and declarations - Type III environmental declarations"	
In compliance with ISO 14040:2006: "Environmental management - LCA - Principles and framework"	
In compliance with ISO 14044:2006: "Environmental management - LCA - Requirements and guidelines"	
In alignment with EN 15804:2012+A1:2013: "Sustainability of construction works - EPD's - Core rules for the product category of construction products"	