

Pass and Seymour 20A 125V Heavy Duty Hospital-Grade Decorator Duplex Receptacle, Ivory Part No. 26362HGI

Heavy-Duty Decorator Hospital Grade Duplex Receptacle Back and Side Wire 20A 125V



continuous +60°C, minimum -40°C without impact

Features & Benefits

Corrosion-resistant, plated steel strap locked into assembly to prohibit strap from bending away from body.	Heavy-duty compact design for easier installation and long lasting performance.
Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.	Impact-resistant nylon face.
Terminal compartments isolated from each other for positive conductor containment.	All devices fit standard #26 opening wall plate.
Tri-drive terminal and mounting screws.	Auto-ground clip assures positive ground.
Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of	

overload at 150% of rated current with direct current. Operating Temperature: Maximum

Specifications

General Info

Product Line	Pass & Seymour	Color	lvory
UPC Number	785007785579	Country Of Origin	Mexico
Number of Receptacles	2	Application Sector	Commercial, Hospital Grade
Standard	UL498, cUL CSA, FEDSPEC	Warranty Type	1-Year Limited Warranty
Туре	Outlet		

Dimensions

Product Width US	1.322 in	Product Depth US	0.833 in			
Product Height US	2.635 in					
Listing Agencies / 3rd Party Agencies						
cULus ListingNumber	140596	cULus Listed	Yes			
Technical Information						
Dielectric Strength	Withstands 2000V minimum	Connection	Back and side wire			
Number of Wires	3	Temperature Rating	-40° - 60° C			
Amperage	20 A	Number of Poles	Double Pole			
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor			
Environmental Conditions	Flammability: UL94 V2					