

Wiremold Discontinued - 4AT Prewired Dual Service Controlled Receptacle EvolutionTM Poke-Thru Device-Aluminum Part No. 4ATCP2CRAL



Designed for retrofit and new construction, Evolution Series 4" Poke-Thru devices provide convenient access to power, communications, and audio/video services recessed below floor level - providing maximum device protection. 2-gangs of capacity allow you to configure services for the needs of your space. Evolution Series 4" Poke-Thru devices are the perfect fit for kiosks, training rooms, classrooms, healthcare facilities or commercial buildings with open-space architecture.

Features & Benefits

Prewired assembly: Save on labor with a completely assembled, prewired poke-thru .	Controlled receptacles: The only option on the market with two marked receptacles in a 4'' poke-thru that also meets Title 24 Plug Load Control standards.
Recessed devices: All power, communications and A/V devices are recessed below floor level, providing maximum protection and device longevity.	Step-on-it installation: Quick and easy installation without the need for additional fasteners or a second installer.
Unique cover design: The cover opens a full 180 degrees with two unique spring-loaded slide egress doors to keep wires, connections and people safe.	Evolution Series Poke-Thru Devices are available in multiple finishes, (BK) black, (GY) gray, (NK) nickel, (BS) brass, (BZ) bronze, (AL) aluminum, (AA) brushed aluminum, (SB) satin brass, and (SN) satin nickel to seamlessly match your environment.
Surface style cover assemblies: A surface style cover is for mounting on top of the finished floor surface. The surface cover is designed to be used for carpet, tile, wood, polished concrete, or terrazzo.	Open system for expanded compatibility: Accepts industry standard power, communications and A/V devices from most manufacturers including Legrand AVIP, Extron® and more.
2 hour fire rating: Evolution Series Poke-Thru Devices use an intumescent material that maintains the fire rating of any floor for up to 2 hours.	Wide trim flange is designed to meet the ADA Accessibility Guidelines as it pertains to ADA Standard 4.5 which addresses changes in floor and ground surface levels. The poke-thru trim flanges are beveled so the slope is no greater than 1:2 ratio.
UL Listed and UL fire classified to U.S. and Canadian safety standards: UL Fire rated for up to 2-hour rated floors maintains the fire classification of the floor.	5
Specifications	

Product Line	Wiremold	Replaced by Part Number	4ATCP2CRAA
UPC Number	786564090823	Country Of Origin	United States
Construction	Assembled	Number of Knockouts	10

General Info

Application Sector	Commercial	Standard	cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes and Fittings Classified for Fire Resistance: File R8209 Guide CEYY. Meets Article 300.21 300.22[C] and 314 of NEC.			
Туре	Poke-Thru					
Dimensions						
Cubic Capacity	24.5 in ³					
Listing Agencies / 3rd Party Agencies						
cULus ListingNumber	E2961	cULus Listed	Yes			
Trade Programs						
USMCA	Yes					
Additional Information						
RoHS Compliant	Yes	Product Environmental Profile	Yes			
Technical Information						
Cable Entry	3/4 in trade size conduit for power	Number of Outlets	2			