

## Wiremold 4FFATC15-LJB Flush Furniture Feed Poke-Thru Unit

Part No. 4FFATC15AL-LJB



Complete with one-piece finish flange and conduit assembly. Conduit assembly consists of one 3/4" trade size conduit and one 1 1/2" trade size conduit. Finish cover flange provided with one 3/4" and one 1 1/2" trade size screw plug opening.

## Features & Benefits

Integral design component that prevents water, dirt and debris from entering power and communication compartments.

Provides one 3/4" opening for power and one 1 1/2" opening for communication cabling. Provides largest dual service capacity for furniture feed applications in the industry. UL Listed for both power and communication furniture feed applications.

Suitable for use in air handling spaces in accordance with Sec. 300-22 (C) of the National Electrical Code.

UL Listed and UL Fire Classified to U.S. and Canadian safety standards for tile and terrazzo. Includes the new UL requirements under UL514A and UL514C for the scrub water exclusion test for carpet and wood floors..

Step-on-it installation. Quick and easy installation without the need for additional fasteners or the need for a second installer.

Whenever you see the TopGuard protection icon on any Wiremold product, you'll know it meets and exceeds UL scrub water exclusion requirements for tile and carper floors.

## Specifications

## General Info

Product Line	Wiremold	UPC Number	786564085461
Country Of Origin	Mexico	Construction	Assembled
Cover Style	Flush, Furniture Feed	Application Sector	Commercial, Education, Healthcare, Hospitality
Standard	UL Fire Classified, cULus, NEC	Warranty Type	1-Year from Installation or 2-Years from Day of Sale
Туре	Poke-Thru		

Dimensions				
Product Width US	8.25 in	Product Weight US	4.64 lb	
Product Depth US	9.688 in	Core Hole Size	4 in	
Knockout Size	1-1/2 in, 3/4 in			
Listing Agencies / 3r	d Party Agencies			
cULus ListingNumber	E2961	cULus Listed	Yes	
Trade Programs				
USMCA	Yes			
Additional Information	n			
RoHS Compliant	Yes	Product Environmental Profile	Yes	
Technical Information				
Floor Type	Carpet, Concrete, Tile, Wood	Fire Rating	2 hr	
Cable Entry	Conduit			