

## Pass and Seymour 20A 125V Heavy Duty Spec-Grade Single Receptacle, Back and Side Wire, Gray Part No. 5361GRY

Heavy-Duty Spec Grade Single Receptacle, Back and Side Wire, 20A 125V



## Features & Benefits

Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly.

.032 inch thick, brass, triple-wipe power contacts for lasting retention.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

Impact-resistant nylon face and thermoplastic back body.

Internal screw-pressure-plate back wire capable of accepting #14 - #10 AWG solid or stranded copper or copper-clad wire.

Terminal compartments isolated from each other for positive conductor containment.

Auto-ground clip assures positive ground.

For covering patents, see www.legrand.us/patents.

For compatible wall plate options, from our screwless plates to our metal wall plates, click here.

Temperature Rise: Maximum 30°C temperature rise at full-rated current TradeMaster unbreakable plates to our radiant after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

## Specifications

## General Info

Product Line	Pass & Seymour	Color	Gray
Finish	Matte	UPC Number	785007536133
Country Of Origin	Mexico	Number of Receptacles	1
Application Sector	Commercial	Standard	UL498, CSA C22.2 No. 42, FEDSPEC
Warranty Type	1-Year Limited Warranty	Туре	Outlet

Dimensions				
Product Width US	1.32 in	Product Depth US	1.093 in	
Product Height US	1.68 in			
Listing Agencies / 3rd Party Agencies				
cUL ListingNumber	140596	cUL Listed	Yes	
Technical Information				
Dielectric Strength	Withstands 2000V minimum	Temperature Rating	-40° - 60° C	
Amperage	20 A	Number of Poles	Double Pole	
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor	