

Quiktron Q-Series Patch Cords, CAT6, booted, Green, 100 FT

Part No. 576-120-100



Q-Series patch cords are a perfect solution for when cost and speed of delivery are top priority. Designed to perform to TIA-568.2-D standards, Q-Series cords are available in a full range of colors and lengths, stocked and ready to order.

Features & Benefits

Connector: 50micron gold plated RJ45 male to

male

Warranty Type: Lifetime warranty

Standards Compliant: Perform to TIA-568.2-D

standards

Conductor: 24AWG stranded copper

Price Sensitive: Perfect solution for when cost and speed of delivery are

top priority

Specifications

General Info

| Product Line | Quiktron | Color | Green |
|-------------------|-------------------|--------------------|------------------------|
| UPC Number | 884815779944 | Country Of Origin | Vietnam |
| Features | Standard Diameter | Application Sector | Commercial, Industrial |
| Warranty Type | 5-Year | Туре | Copper Patch Cord |
| Dimensions | | | |
| Product Weight US | 2.5 lb | Product Length US | 100.0 FT |
| Cable Length | 100 ft | | |
| | | | |

Additional Information

| RoHS Compliant | Yes | | |
|-----------------------------|-------------------------------|---------------------------|-------------------------------|
| Technical Information | | | |
| Jacket Material | PVC | Operating Temperature Min | -10 °C |
| Category Performance Rating | Cat6 | Compatibility | RJ-45 |
| Wire Gauge | 24 AWG | Storage Humidity | 0-90% RH (Non- Condensing) |
| Plating Specification | 50 μ in Gold | Jacket Application | Riser Rated |
| Bend Radius | 0.896 in | Shielded/Unshielded | Unshielded |
| Termination Style | Pre-Terminated | Conductor Stranding | Stranded |
| Operating Temperature Max | 60 °C | Cable Type | Snagless |
| Jacket Rating | CM Rated | Cable Diameter | 0.224 in |
| Braid | Non-braided Wiring | Connector 2 | RJ-45 Male |
| Connector 1 | RJ-45 Male | Operating Temperature | -10°-60°C |
| Operating Humidity | 0-90% RH (Non- Condensing) | Conductor Material | Copper |
| Voltage | 300.0 V | Storage Temperature | -40° - 60° C |