



Pass and Seymour

Hospital Grade Short Strap Single Receptacles, Back & Side Wire, 15A, 125V, White

Part No. 8284W

□

Hospital Grade Short Strap Single Receptacle Back & Side Wire 15amp 125volt.

Features & Benefits

- Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly.
- One-piece brass, triple-wipe power contacts for lasting retention.
- Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
- Impact-resistant nylon face and thermoplastic back body.
- Internal screw-pressure-plate back wire capable of accepting #14 : #10 AWG solid or stranded copper or copper-clad wire.
- Terminal compartments isolated from each other for positive conductor containment.
- Tri-drive terminal and mounting screws.
- Auto-ground clip assures positive ground.
- For covering patents, see www.legrand.us/patents.
- For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

Specifications

General Info

Color	White	UPC Number	785007378610
Country Of Origin	Mexico	Product Line	Pass & Seymour
Application Sector	Hospital Grade	Standard	UL498, cUL/CSA C22.2 No. 42

Technical Information

Number of Poles	Double Pole	Voltage	125 V
Connection	Back and side wire	Dielectric Strength	Withstands 2000V minimum
Temperature Rating	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact	Wire Size	14 to 10 AWG
Number of Wires	3	Indoor/Outdoor	Indoor
Environmental Conditions	Flammability: UL94 V2		