

Heavy-Duty Hospital Grade Compact Design Duplex Receptacle Back and Side Wire 20A 125V

Features & Benefits

Impact-resistant nylon face. .032 inch thick, brass, triple-wipe power contacts for lasting retention.

Easily accessible break-off line contact connecting tab for split circuit wiring.

Corrosion-resistant, zinc-plated steel strap is locked in.

Internal screw-pressure-plate back wire and side wire line terminals accept #14 : #10

High strength thermoplastic back body.

Auto-ground clip assures positive ground.

AWG copper or copper-clad conductors.

Compact design for easy installation.

Tri-drive terminal and mounting screws.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Specifications

General Info

Product Line	Pass & Seymour	Color	lvory
	1 uss a seymour		
Finish	Matte	UPC Number	785007830033
Country Of Origin	Mexico	Number of Receptacles	2
Application Sector	Commercial, Hospital Grade	Standard	UL 498, FEDSPEC
Warranty Type	1-Year Limited Warranty	Туре	Outlet
Dimensions			

Product Depth US

0.78 in

1.322 in

Product Width US

Product Height US	3.281 in			
Listing Agencies / 3rd Party Agencies				
cULus ListingNumber	140596	cULus Listed	Yes	
Technical Information				
Amperage	20 A	Number of Poles	Double Pole	
Wire Size	4 AWG	Indoor/Outdoor	Indoor	