

## Wiremold 8CT Evolution™ Poke Thru Flush Style Cover, Black Part No. 8CT2BK

Flush style die-cast aluminum cover assembly in powder-coated black finish. 8CT2 Series cover assemblies designed for use with 8STCP, 8STC, and 8STCPAV Poke-Thru Stem Assemblies. NOTE: Add suffix "TR" to the end of the part number to indicate tamper-resistant cover assembly.

## Features & Benefits

"Die-cast aluminum cover assemblies: The new Evolution Series poke-thru design includes all metal die-cast aluminum cover assemblies, with two unique spring-loaded slide egress doors. No clumsy flip lids to get broken or cause an added trip hazard. Unique cover design: The cover opens a full 180 degrees with two unique spring-loaded slide egress doors to keep wires, connections and people safe. Flush style cover assemblies: A flush style cover for tile applications allows the Evolution Series Poke-Thru Devices to be adjusted to the same level as the top surface of the floor covering. The flush cover is designed to be used for tile or wood floors and in higher traffic applications, where a low profile is a must. Multiple finishes: Evolution Series Poke-Thru Devices are available in multiple finishes, (BK) black, (GY) gray, (NK) nickel, (BS) brass, (BZ) bronze, (AL) aluminum, (AA) brushed aluminum, (SB) satin brass, and (SN) satin nickel to seamlessly match your environment.

## **Specifications**

General Info			
Product Line	Wiremold	Color	Black
UPC Number	786564089407	Country Of Origin	India
Application Sector	Commercial	Standard	cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC
Туре	Cover		
Dimensions			
Product Width US	9.25 in	Product Weight US	4.16 lb

Product Volume US	99.25 cu in	Product Depth US	1.16 in	
Product Height US	9.25 in	Core Hole Size	8 in	
Listing Agencies / 3rd Pa	rty Agencies			
cULus ListingNumber	E2961	cULus Listed	Yes	
Additional Information				
RoHS Conformant	Yes			
Technical Information				
Number of Outlets	0			