


adorne Collection adorne® 15A Single Tamper-Resistant Outlet, Magnesium Part No. ARTR151M10



Designed with the same commitment to style and safety as the entire adorne Collection, this device is ideal as a dedicated outlet for large or stationary appliances, or in small or narrow areas where a single plug is needed. The single outlet features "invisi-shutters" for discreet tamper-resistance that keeps children safe without compromising on style.

Made exclusively for use with screwless Wall Plates from the adorne® Collection, sold separately.

Features & Benefits

For complete installation, device must be paired with an adorne® screwless Wall Plate (not included). Available in a range of contemporary colors and stunning finishes.

Replaces a standard outlet with ease in as little as 10 minutes.

Creates a designated outlet, ideal for use with appliances or products and devices with larger plugs.

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

Specifications

General Info Product Line Pass & Seymour Color Magnesium Finish Frosted **UPC** Number 785007404340 Country Of Origin China Number of Receptacles Device Front Face Size Full-Size Device Backbody Size Full-Size Outlet Type **Application Sector** Residential Tamper-Resistant Limited Lifetime RoHS, CSA, cULus, UL, Conforms to Standard Warranty Type NFMA WD-1 and WD-6 Warranty Single, Tamper-Resistant Type

Dimensions			
Product Length US	1.33 in		
Listing Agencies / 3rd P	Party Agencies		
CSA Listed	Yes	cULus Listed	Yes
CSA File Number	C22.2 No.42		
Additional Information			
RoHS Compliant	Yes		
Technical Information			
Seismic Tested	No	Connection	Wired
Amperage	15 A	Current Rating	15 A
Indoor/Outdoor	Indoor	Wattage	1875 W
Mounting Type	Box	Connection Type	Internal Pressure Plate
Environmental Conditions	Flammability Rating: UL 94 V2		