

Pass and Seymour 20A 125V Commercial Spec-Grade Duplex Receptacle, Side Wire, Brown Part No. CR20

rait No. Cixzo



Commercial Spec Grade Duplex Receptacle, Side Wire 20A 125V

Features & Benefits

Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly.

.032 inch thick, brass, triple-wipe power contacts for lasting retention.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

Impact-resistant nylon face and thermoplastic back body.

Accepts #14 - #10 AWG solid or stranded copper or copper-clad wire.

Terminal compartments isolated from each other for positive conductor containment.

Auto-ground clip assures positive ground.

For covering patents, see www.legrand.us/patents.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +50°C, minimum -40°C without impact

Specifications

General Info

| Pass & Seymour | Color | Brown |
|-------------------------|---------------------------|---|
| Matte | UPC Number | 785007119121 |
| Mexico | Number of Receptacles | 2 |
| Commercial | Standard | UL 498 |
| 1-Year Limited Warranty | Туре | Outlet |
| | Matte Mexico Commercial | Matte UPC Number Mexico Number of Receptacles Commercial Standard |

| Dimensions | | | | |
|---------------------------------------|-------------|------------------|-------------|--|
| Product Width US | 1.322 in | Product Depth US | 0.78 in | |
| Product Height US | 2.635 in | | | |
| Listing Agencies / 3rd Party Agencies | | | | |
| cULus ListingNumber | 140596 | cULus Listed | Yes | |
| Additional Information | | | | |
| Product Environmental Profile | Yes | | | |
| Technical Information | | | | |
| Amperage | 20 A | Number of Poles | Double Pole | |
| Wire Size | 14 - 10 AWG | Indoor/Outdoor | Indoor | |
| | | | | |