



Construction Spec Grade Duplex Receptacle Back and Side Wire 20A 125V

Features & Benefits

Corrosion-resistant, plated steel strap locked ir to face and back body to resist pulling away from face/body assembly.	n Triple-wipe brass contacts ensure lasting, positive contact with plug blades.
Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring	Impact-resistant nylon face and thermoplastic back body.
8 hole internal screw-pressure-plate back wire terminals accept #10 - #14 AWG solid or stranded copper or copper-clad conductors.	Terminal compartments isolated from each other for positive conductor containment.
Auto-ground clip assures positive ground.	For covering patents, see www.legrand.us/patents.
For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.	

Specifications

General Info

Pass & Seymour	Color	Gray
Matte	UPC Number	785007210262
Mexico	Number of Receptacles	2
Commercial	Standard	UL 498, FEDSPEC
1-Year Limited Warranty	Туре	Outlet
	Matte Mexico Commercial	MatteUPC NumberMexicoNumber of ReceptaclesCommercialStandard

Dimensions					
Product Width US	1.322 in	Product Depth US	0.78 in		
Product Height US	2.635 in				
Listing Agencies / 3rd	Party Agencies				
cULus ListingNumber	140596	cULus Listed	Yes		
Technical Information					
Amperage	20 A	Number of Poles	Double Pole		
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor		