

Pass and Seymour 30A NEMA L1230 Single Receptacle

Part No. L1230R

Turnlok® Single Receptacle, 3-Wire 30A 3-Phase 480V



Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Yes

Side and external screw-pressure-plate back wire capability.

Specifications

General Info			
Product Line	Pass & Seymour	Color	Black
Country Of Origin	Mexico	Application Sector	Commercial
Standard	UL 498		
Dimensions			
Product Width US	1.61 in	Product Depth US	1.28 in
Product Height US	2.42 in		

cULus Listed

cULus ListingNumber

Listing Agencies / 3rd Party Agencies

140596

Additional Information			
Product Environmental Profile	Yes		
Technical Information			
Phase	3	Number of Wires	3
Amperage	30 A	Number of Poles	3-Way
Wire Size	18 - 10 AWG	Voltage	480.0 V