



Wattstopper
DLM Segment Network Wire, 2000 Spool
Part No. LM-MSTP-S2000



This type of wire connects low voltage devices (i.e., switches, occupancy sensors, photocells) to panels. It is #20 AWG wire that meets UL and NEC standards for Class 2 applications. Plenum rated wire meets plenum and riser requirements. Several types of multi-conductor low voltage wires are available for standard, pilot, locator, and multilevel switching or for connecting photocells to the LI control panels. This wire can also be used to wire relays remotely

Features & Benefits

Data communications wire provides communications between panels and signaling devices

Custom cut to specified lengths

Distance markings in foot increments

Low voltage component wire connects switches, sensors, and other low voltage devices to panels

Color-coded for streamlined installation

Specifications

General Info

| | | | |
|--------------------|--------------|-------------------|---------------|
| Product Line | Wattstopper | Color | Green |
| UPC Number | 754182938247 | Country Of Origin | United States |
| Product Series | LM-MSTP | Jacket Color | Light Green |
| Application Sector | Commercial | Standard | UL, cUL |
| Warranty Type | 5-Year | Type | Cable, Spool |

Dimensions

| | | | |
|-------------------|-----------|--------------|---------|
| Product Length US | 2000.0 FT | Cable Length | 2000 ft |
|-------------------|-----------|--------------|---------|

Technical Information

| | | | |
|-----------------|-----|------------|--------|
| Jacket Material | PVC | Wire Gauge | 22 AWG |
|-----------------|-----|------------|--------|

| | | | |
|--------------------|----------------------------------|---------------------|----------|
| Jacket Application | Plenum Rated | Shielded/Unshielded | Shielded |
| Conductor | 1.5-Pair | Protocol | MS/TP |
| Jacket Rating | CL3P Rated, CMP Rated, FT6 Rated | Temperature Rating | 75° C |
| Cable Diameter | 0.185 in | Indoor/Outdoor | Indoor |