

Wiremold NM20GB512 Nonmetallic Plugmold® Multioutlet System Part No. NM20GB512



5' Plugmold Plus Multioutlet Strip comprised of five 12 inch parts, GB 15 Amp

Features & Benefits

Nonmetallic, lightweight with snap-on cover. Speeds installation: provides easy access to wiring for changes or additions.

Full range of fittings. Facilitates easy installation of wiring for whatever the job: communication workstation outlets, receptacles, switches and more. Over lapping fittings permit neat butting to raceway.

NEMA heavy duty duplex receptacles independently tested to Fed. Spec. WC596G performance criteria. Enhanced product quality ensures dependable performance.

Snapicoil harnesses offer a choice of receptacle spacing. Center spacing between receptacles of 12", 18" and 30".

Customization available. All products can be modified to accommodate virtually any application.

Tapered profile design with textured ivory finish. Blends with surroundings in office, display space, dorm rooms and residential locations.

Factory wired harness available with duplex receptacles on multiple spacings. Maximum power distribution to the point of use.

Snapicoil harnesses of prewired receptacles in 48' and 50'. Eliminates the need for multiple splicing, speeding up installations on long runs.

Field replaceable surge module. No need to remove the raceway cover to splice in a replacement receptacle. Field changes and maintenance are quick and easy.

Specifications

General Info

| Product Line | Wiremold | UPC Number | 786776519990 |
|-------------------|---------------|-----------------------|--------------|
| Country Of Origin | United States | Number of Receptacles | 5 |

| Dimensions Product Width US 1.75 in Product Depth US 1.0 in Product Length US 1.75 in Listing Agencies / 3rd Party Agencies cULus ListingNumber E15191 cULus Listed Yes Buy American Act Compliance NAFTA Yes Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | Application Sector | Commercial | Standard | cULus Listed Base & Blank Cover: File E90378 Guide RJBT. Multioutlet Assemblies: File E15191 Guide PVGT. Fittings: File E90377 GuideRJPR. Base & Blank Cover & Plugmold Series w/Snapcoil Harness: Meets Article 386 of NEC. Meets Section 12-3032 of CEC. Plugmold Wired Sections: Meets Article 380 of NEC. Meets Section 12-3032 of CEC. |
|--|----------------------------|-------------|--------------------------|---|
| Product Width US 1.75 in Product Depth US 1.0 in Product Length US 1.75 in Listing Agencies / 3rd Party Agencies CULus ListingNumber E15191 CULus Listed Yes Buy American Act Compliance NAFTA Yes Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | Гуре | Plugmold | | |
| Product Length US 1.75 in Listing Agencies / 3rd Party Agencies cULus ListingNumber E15191 cULus Listed Yes Buy American Act Compliance NAFTA Yes Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | Dimensions | | | |
| Listing Agencies / 3rd Party Agencies cULus ListingNumber E15191 cULus Listed Yes Buy American Act Compliance NAFTA Yes Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | Product Width US | 1.75 in | Product Depth US | 1.0 in |
| CULus ListingNumber E15191 cULus Listed Yes Buy American Act Compliance NAFTA Yes Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | Product Length US | 1.75 in | | |
| Buy American Act Compliance NAFTA Yes Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | _isting Agencies / 3rd Par | ty Agencies | | |
| Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | :ULus ListingNumber | E15191 | cULus Listed | Yes |
| Additional Information RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | Buy American Act Compli | ance | | |
| RoHS Conformant Yes Technical Information Amperage 15 A Enclosure Type Non-Metallic | NAFTA | Yes | | |
| Technical Information Amperage 15 A Enclosure Type Non-Metallic Dry interior locations | Additional Information | | | |
| Amperage 15 A Enclosure Type Non-Metallic | RoHS Conformant | Yes | | |
| Dry interior locations | Technical Information | | | |
| Dry interior locations | Amperage | 15 A | Enclosure Type | Non-Metallic |
| Voltage 120.0 V Environmental Conditions | /oltage | 120.0 V | Environmental Conditions | Dry interior locations |