

Cablofil SB-5A12C-S120-30 AL 5H SOLBOT 120L 30W

Part No. P300614



The aluminum I-beam design of ITray is perfect for industrial installations with large diameter cables in long span situations, minimizing total tray width and creating a smooth transition between straight sections and fittings. A structural offset in the sidewall creates strong, mid-span splices that need fewer supports. Each splice snaps in place and stays without holding, Additionally, only four bolts are needed for each splice reducing hardware needs by 50%. These features allow Itray to be installed up to 30% faster than standard tray.

Features & Benefits

Material: Aluminum Alloy 6063-T6 Finish: Plain

Bottom: Ldr: 1" wide I rung SB: Flat Sheet over 12" Rung Spacing.

Construction: Welded

SC:Solid Corrugated VC: Vented Corrugated

Tray Design: Tray construction and markings are per the latest edition

of NEMA Standards Publication VE1, CSA C22.2 No. 126.

Tray Grounding Capability: Classified as an equipment grounding conductor per NEC 392.60.

Specifications

Cablofil	Finish	AL
800388064799	Country Of Origin	Mexico
31.5 in	Product Weight US	36.405 lb
11.288 cu ft	Product Depth US	120.0 in
5.16 in		
ance		
Yes		
	800388064799 31.5 in 11.288 cu ft 5.16 in	800388064799 Country Of Origin 31.5 in Product Weight US 11.288 cu ft Product Depth US 5.16 in