

## Pass and Seymour SteriGuard<sup>TM</sup> Antimicrobial Female Watertight Cap for 15A 20A Straight Blade and 15A Locking Devices Part No. PS15WTAM



SteriGuard Anti-Microbial Wiring Devices provide excellent protection against the growth of microbes on all surfaces. Independent testing proves the ability of these devices to inhibit the growth of Escherichia coli, Gram (-) and Staphylococcus aureus, Gram (+) providing long lasting benefits to manufacturers beyond conventional cleaning methods. SteriGuard provides a cost-effective way to add additional safety precautions and unequaled assurance that every feasible step has been taken in the interest of consumer protection.

(without impact) to +60°C continuous UV resistance All exposed material s are UV

stabilized

## Features & Benefits

UL and CSA Listed		NS	SF (National Sanitation Foundation) Certified
Patent Pending			ti-microbial Additives Embedded in polymer and nibits Growth of Bacteria, Molds, Mildews and Fur
Anti-microbial Additive Resistant to Scuffing and Cleaning			cherichia (E.Coli): - Log reduction greater than 4 duced surface bacteria by greater than 99.99%
Staphylococcus (Sta than 99.97%	ph), MRSA: - Log Reduction greater than 4.3, r		lmonella : Log Reduction Greater Than 3.6, reduc rface bacteria by Greater Than 99.97%
RoHS Compliant (Non-Halogenated)			dependently tested and Certified to JIS Z2801 andards
Resistant to High Pressure Hose-down applications		То	ngue & Groove Environmental Sealing
Keyed Body and Cover for Alignment		NE	EMA Type 4, 4x, 6, 6P and IP67 Protection
	robial Wiring Devices are ideal for a wide rang ration, procession, & packaging: agriculture, p		
Specifications			
General Info			
Product Line	Pass & Seymour	Color	Yellow
UPC Number	785007056938	Country Of Origin	United States
Standard	UL Listed, CSA Listed		
Technical Informa	tion		
Amperage	15 A	Environmental Conditions	Moisture Resistance NEMA 4, 4X, 12, 6, 6P/IP65, 66, 67 (Plug & Connector only) Flammability UL94V0 (boxes & wiring device interiors) Operating Temperature -40°C
13 -	· <del>-</del> · *		( : 1