

Pass and Seymour SteriGuardTM Antimicrobial Female Watertight Cap for 15A|20A Straight Blade and 15A Locking Devices Part No. PS15WTAM



SteriGuard Anti-Microbial Wiring Devices provide excellent protection against the growth of microbes on all surfaces. Independent testing proves the ability of these devices to inhibit the growth of Escherichia coli, Gram (-) and Staphylococcus aureus, Gram (+) providing long lasting benefits to manufacturers beyond conventional cleaning methods. SteriGuard provides a cost-effective way to add additional safety precautions and unequaled assurance that every feasible step has been taken in the interest of consumer protection.

Environmental Conditions interiors) Operating Temperature -40°C

stabilized

(without impact) to +60°C continuous UV resistance All exposed material s are UV

Features & Benefits

UL and CSA Listed			NSF (National Sanitation Foundation) Certified
Patent Pending			Anti-microbial Additives Embedded in polymer and inhibits Growth of Bacteria, Molds, Mildews and Fung
Anti-microbial Additive Resistant to Scuffing and Cleaning			Escherichia (E.Coli): - Log reduction greater than 4.8, reduced surface bacteria by greater than 99.99%
Staphylococcus (Staph), MI than 99.97%	RSA: - Log Reduction greater than 4.3, r	educes surface bacteria by gre	eater Salmonella : Log Reduction Greater Than 3.6, reduce: surface bacteria by Greater Than 99.97%
RoHS Compliant (Non-Halogenated)			Independently tested and Certified to JIS Z2801 standards
Resistant to High Pressure Hose-down applications			Tongue & Groove Environmental Sealing
Keyed Body and Cover for Alignment			NEMA Type 4, 4x, 6, 6P and IP67 Protection
=	Wiring Devices are ideal for a wide rand procession, & packaging: agriculture, p		
Specifications			
General Info			
Product Line	Pass & Seymour	Color	Yellow
Country Of Origin	United States	Standard	UL Listed, CSA Listed
Technical Information			
			Moisture Resistance NEMA 4, 4X, 12, 6, 6P/IP65, 66, 67 (Plug & Connector only) Flammability UL94V0 (boxes & wiring device

Amperage

15 A