

### Pass and Seymour Sloped-Roof Stainless Steel Safety Switch with Auxiliary Contact, 100A Part No. PSDS100AXSR



100 Amps Sloped-Roof Stainless Steel Safety Switch with Auxiliary Contact.Legrands 316-Grade Sloped-Roof Stainless Steel Safety Switches are designed to provide superior corrosion resistance in harsh environments like food and beverage processing plants where wash down/hose down at extreme temperatures is a daily necessity, as well as environments where salts, acids, and chemicals are prevalent. Legrands Sloped-Roof Stainless Steel Safety Switches with NEMA 4X/12, IP66, 67, and 69K ratings are the best solution for durability and personnel safety in any environment.

# Features & Benefits

| Type 316 grade stainless steel provides superior resistance to corrosion.  | 6 conduit entry points for flexible installation options.  |
|--|--|
| Certified by the National Sanitation Foundation (NSF) for hygiene requirements in food & beverage processing.  | Can accommodate up to 3 sets of auxiliary contacts for control circuit applications.                       |
| 15: sloped roof helps to facilitate run-off and minimize the harborage of contaminants.  | 3/4" standoffs on mounting feet allow adequate space for runoff and inspection behind the switch.          |
| Water- and dust-tight enclosure rated NEMA 3R, 4, 4X,12K and IP66,67,69 f<br>protection against high-pressure, high-temperature water from multiple<br>directions. | for High-visibility yellow and red handle can be<br>padlocked to meet OSHA lockout/tagout<br>requirements. |
| OSHA-compliant Lockout/Tagout.   | Multiple drill points for ease of installation (each side and back).                                       |
| Captive cover screws.  | No labels on cover, stamped-in ON/OFF.   |
| Inability to remove cover when in ON position.   | Compact footprint.   |
|  |  |

# Specifications

## General Info

| Product Line      | Pass & Seymour | UPC Number         | 785007133714 |
|-------------------|----------------|--------------------|--------------|
| Country Of Origin | United States  | Application Sector | Industrial   |
| Туре              | Safety Switch  |                    |              |

### Dimensions

| Product Width US                      | 8.3 in   | Product Depth US | 7.1 in        |  |  |
|---------------------------------------|----------|------------------|---------------|--|--|
| Product Height US                     | 14.03 in |                  |               |  |  |
| Listing Agencies / 3rd Party Agencies |          |                  |               |  |  |
| cULus Listed                          | Yes      |                  |               |  |  |
| Technical Information                 |          |                  |               |  |  |
| Amperage                              | 100 A    | Wire Size        | #14 - #10 AWG |  |  |