

Pass and Sevmour PlugTail® 15A 125V Heavy-Duty Spec Grade Single Receptacles, White Part No. PT5261W



Plugtail Heavy-Duty Spec Grade Single Receptacles with Side and Back Wire install 5x faster than conventional wiring devices.

In the world of commercial wiring device installation, it's all about flexibility. For years now, PlugTail® electrical wiring devices have been providing that flexibility in commercial buildings everywhere. Easy to install, change out and upgrade, PlugTail allows you to continuously reconfigure to meet a building's electrical requirements as the space transforms – without the time and expense of rewiring. It's a cost-effective, code-compliant, proven way to keep your customers connected to the future, while securing your reputation as a forward-thinking electrical contractor.

Features & Benefits

PlugTail Devices install up to 5 times faster than traditional No exposed terminals create a finger-safe application before, devices. during and after installation.

ensure consistent, reliable electrical connections.

Built-in connector features large brass terminal blades to Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger-safe housing.

Corrosion-resistant, plated steel strap locked in to face and Impact-resistant nylon face and thermoplastic back body. back body to resist pulling away from face/body assembly.

Tri-drive terminal and mounting screws.

Auto-ground clip assures positive ground.

Specifications

General Info			
Product Line	Pass & Seymour	Color	White
Finish	Glossy	UPC Number	785007437867
Country Of Origin	Mexico	Receptacle Type	Straight Blade
Number of Receptacles	1	Outlet Type	Commercial
Application Sector	Commercial	Standard	UL UL498, CSA No.C22.2, FEDSPEC
Warranty Type	1-Year Limited Warranty	Туре	Outlet, Plug Tail, Single

Dimensions

Product Width US	1.546 in	Product Depth US	1.9 in
Product Height US	4.185 in		
Listing Agencies / 3rd	d Party Agencies		
cULus Listed	Yes		
Technical Information	1		
Amperage	15 A	Indoor/Outdoor	Indoor
Mounting Type	Вох	Environmental Conditions	95% (relative humidity, non- condensing)