



PlugTail® Industrial Extra Heavy-Duty Spec Grade Receptacles, 15A, 125A

Features & Benefits

.036 inch thick, brass, triple-wipe power contacts for lasting retention.

Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.

Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.

Pre-stripped connector leads fasten to conductors, easier than standard pigtailed.

For covering patents, see www.legrand.us/patents.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current.
Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

No exposed terminals create a finger safe application before, during, and after installation.

Crimped and welded contacts.

Large brass contacts snugly terminate on device blade terminals.

Auto-ground clip assures positive ground.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click [here](#).

PlugTail™ Connector: #12 AWG, THHN, copper conductor, 6" leads, stripped, solid or stranded, for use with PlugTail Receptacles only

Specifications

General Info

| | | | |
|-------------------|----------------|--------------------|------------|
| Product Line | Pass & Seymour | Color | Brown |
| Country Of Origin | Mexico | Application Sector | Commercial |
| Standard | cULus UL498 | | |

Dimensions

| | | | |
|------------------|----------|------------------|----------|
| Product Width US | 1.625 in | Product Depth US | 0.866 in |
|------------------|----------|------------------|----------|

| | |
|-------------------|---------|
| Product Height US | 2.75 in |
|-------------------|---------|

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140596 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Technical Information

| | | | |
|---------------------|--------------------------|-----------------|---|
| Dielectric Strength | Withstands 2000V minimum | Number of Wires | 3 |
|---------------------|--------------------------|-----------------|---|

| | | | |
|--------------------|--------------|----------|------|
| Temperature Rating | -40° - 60° C | Amperage | 15 A |
|--------------------|--------------|----------|------|

| | | | |
|-----------------|-------------|-----------|--------|
| Number of Poles | Double Pole | Wire Size | 12 AWG |
|-----------------|-------------|-----------|--------|

| | | | |
|---------|---------|--------------------------|-----------------------|
| Voltage | 125.0 V | Environmental Conditions | Flammability: UL94 V2 |
|---------|---------|--------------------------|-----------------------|
