

Pass and Seymour **PlugTail® 20A 125V Spec-Grade Duplex Receptacle, Gray** Part No. PT5362GRY

PlugTail® Spec Grade Receptacles, 20A, 125V PlugTail® devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.



## Features & Benefits

.036 inch thick, brass, triple-wipe power contacts for lasting retention.	Plated steel wrap strap design for maximum durability and corrosion resistance.
No exposed terminals create a finger safe application before, during, and after installation.	Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.
Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.	Crimped and welded contacts.
Pre-stripped connector leads fasten to conductors, easier than standard pigtails.	Auto-ground clip assures positive ground.
For covering patents, see www.legrand.us/patents.	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact
PlugTail <sup>™</sup> Connector: #12 AWG, THHN, copper conductor, 6" leads, stripped, solid or stranded, for use with PlugTail Receptacles only	

## Specifications

## General Info

Product Line	Pass & Seymour	Color	Gray
Finish	Matte	UPC Number	785007091687
Country Of Origin	Mexico	Number of Receptacles	2
Application Sector	Commercial	Standard	UL 498, FEDSPEC

Warranty Type	1-Year Limited Warranty	Туре	Outlet			
Dimensions						
Product Width US	1.5 in	Product Depth US	0.625 in			
Product Height US	2.75 in					
Listing Agencies / 3rd Party Agencies						
cULus Listed	Yes					
Technical Information						
Amperage	20 A	Number of Poles	Double Pole			
Wire Size	4 AWG	Indoor/Outdoor	Indoor			