



These durable, dependable receptacles feature a permanently marked, differentiated solution that meets all necessary code requirements. For detailed PlugTail® information, visit our PlugTail® Headquarters. For detailed Tamper-Resistant receptacle information, visit our Tamper-Resistant Receptacles page.

Features & Benefits

| | |
|--|---|
| .032 inch thick, brass, triple-wipe power contacts for lasting retention. | Plated steel wrap strap design for maximum durability and corrosion resistance. |
| No exposed terminals create a finger safe application before, during, and after installation. | Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections. |
| Dual mechanical shutter system to help prevent insertion of foreign objects (TR models). | Permanent controlled markings on face of receptacle compliant with ASHRAE 90.1, CA Title 24, and NEC. |
| Auto-ground clip assures positive ground. | Half-controlled versions include welded, pre-wired lead that control top half of receptacle for split circuit applications. |
| For covering patents, see www.legrand.us/patents . | For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here . |
| Wire Size: #12 AWG THHN | |

Specifications

General Info

| | | | |
|--------------------|----------------|-------------------|--------------------------------------|
| Product Line | Pass & Seymour | Color | Light Almond |
| UPC Number | 785007051803 | Country Of Origin | Mexico |
| Application Sector | Commercial | Standard | UL Listed, CSA Listed, FSUL, FEDSPEC |

Dimensions

| | | | |
|-------------------|----------|------------------|---------|
| Product Width US | 1.322 in | Product Depth US | 0.78 in |
| Product Height US | 2.635 in | | |

Listing Agencies / 3rd Party Agencies

| | |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

Technical Information

| | | | |
|---------------------|--------------------------|---------------------|-----|
| Dielectric Strength | Withstands 2000V minimum | Is Tamper-Resistant | Yes |
|---------------------|--------------------------|---------------------|-----|

| | | | |
|-----------------|--------|--------------------------|--------------|
| Phase | Single | Connection | PlugTail |
| Number of Wires | 3 | Temperature Rating | -40° - 60° C |
| Amperage | 15 A | Number of Poles | Double Pole |
| Wire Size | 12 AWG | Environmental Conditions | UL94 V2 |