



These durable, dependable receptacles feature a permanently marked, differentiated solution that meets all necessary code requirements. For detailed PlugTail® information, visit our PlugTail® Headquarters. For detailed Tamper-Resistant receptacle information, visit our Tamper-Resistant Receptacles page.

## Features & Benefits

| .032 inch thick, brass, triple-wipe power contacts for lasting retention.                     | Plated steel wrap strap design for maximum durability and corrosion resistance.  |
|---|--|
| No exposed terminals create a finger safe application before, during, and after installation. | Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.                                   |
| Dual mechanical shutter system to help prevent insertion of foreign objects (TR models).      | Permanent controlled markings on face of receptacle compliant with ASHRAE 90.1, CA Title 24, and NEC.  |
| Auto-ground clip assures positive ground.   | Half-controlled versions include welded, pre-wired lead that control top half of receptacle for split circuit applications.                      |
| For covering patents, see www.legrand.us/patents.   | For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here. |
| Wire Size: #12 AWG THHN   |  |

## Specifications

## General Info

| Product Line                          | Pass & Seymour | Color             | White                                |  |  |
|---------------------------------------|----------------|-------------------|--------------------------------------|--|--|
| UPC Number                            | 785007051766   | Country Of Origin | Mexico                               |  |  |
| Application Sector                    | Commercial     | Standard          | UL Listed, CSA Listed, FSUL, FEDSPEC |  |  |
| Dimensions                            |                |                   |                                      |  |  |
| Product Width US                      | 1.322 in       | Product Depth US  | 0.78 in                              |  |  |
| Product Height US                     | 2.635 in       |                   |                                      |  |  |
| Listing Agencies / 3rd Party Agencies |                |                   |                                      |  |  |
| cULus Listed                          | Yes            |                   |                                      |  |  |
| Technical Information                 |                |                   |                                      |  |  |
|                                       |                |                   |                                      |  |  |

| Dielectric Strength | Withstands 2000V minimum | Is Tamper-Resistant      | Yes          |
|---------------------|--------------------------|--------------------------|--------------|
| Phase               | Single                   | Connection               | PlugTail     |
| Number of Wires     | 3                        | Temperature Rating       | -40° - 60° C |
| Amperage            | 15 A                     | Number of Poles          | Double Pole  |
| Wire Size           | 12 AWG                   | Environmental Conditions | UL94 V2      |