

Built for the harshest medical environments, Pass and Seymour power indicating receptacles feature two industry-exclusive green LEDs that offer clear visual assurance of power indication at the receptacleeven with critical equipment plugged into the device. The LEDs operate independently from one another to accommodate split-circuit wiring installations. Tamper-resistant protection comes standard with each receptacle to further enhance safety. For detailed PlugTail® information, visit our PlugTail® Headquarters.

Features & Benefits

.036 inch thick, brass, triple-wipe power contacts for lasting retention.

GE Lexan high impact-resistant lens.

before, during, and after installation.

No exposed terminals create a finger safe application Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.

Crimped and welded contacts.

Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.

Pre-stripped connector leads fasten to conductors, easier than standard pigtails.

Auto-ground clip assures positive ground.

For covering patents, see www.legrand.us/patents.

Wire Size: #12 AWG THHN

Specifications

| General Info | | | |
|-----------------------|---|--------------------|----------------------------|
| Product Line | Pass & Seymour | Color | Gray |
| UPC Number | 785007041286 | Country Of Origin | Mexico |
| Number of Receptacles | 2 | Application Sector | Commercial, Hospital Grade |
| Standard | CSA Listed, cULus, FSUL, UL Listed, FEDSPEC | Type | Outlet |
| Dimensions | | | |
| Product Width US | 1.625 in | Product Depth US | 0.866 in |
| Product Height US | 2.75 in | | |

Listing Agencies / 3rd Party Agencies

| cULus Listed | Yes | | | | |
|-----------------------|--------------------------|-----------------|--------|--|--|
| Technical Information | | | | | |
| Dielectric Strength | Withstands 2000V minimum | Phase | Single | | |
| Connection | PlugTail | Number of Wires | 3 | | |
| Temperature Rating | -40° - 60° C | Amperage | 20 A | | |
| Number of Poles | Double Pole | Wire Size | 12 AWG | | |

Environmental Conditions UL94 V2

Indoor/Outdoor

Indoor