


Wiremold FLUSH POKE-THRU ASSY/20A/BK/RT/LJB

Part No. RC7ATCBK-LJB



Flush Style Poke-Thru Devices are an excellent solution for bringing power, communication, and A/V services to the workstation in an open space, above-grade floor environment. All Wiremold Flush Style Poke-Thru Devices come with built-in TopGuard™ protection, an industry-leading design that meets and exceeds UL scrub water exclusion requirements for tile and carpet floors. Topguard protection prevents water, dirt, or debris from entering not just the power devices, but also the communication devices. All Wiremold Flush Style Poke-Thru Devices can be installed on tile, carpet, or wood covered floors. Each of these devices provides an excellent solution for both new or retrofit construction, with typical applications that include office buildings, airports, malls, shopping centers, libraries, and schools.

Features & Benefits

Prewired 20A duplex receptacle can be wired as standard duplex or isolated ground. Wiremold Open System unloaded inserts to accept two discrete keystone connectors from most manufacturers are provided. Includes 2 Cat 6 TechChoice™ discrete keystone connectors and Ortronics® TracJack bezels

Specifications

| General Info | | | | | | | |
|---------------------------------------|--|--------------------|--------------|--|--|--|--|
| Product Line | Wiremold | UPC Number | 786564151517 | | | | |
| Country Of Origin | Mexico | Construction | Assembled | | | | |
| Number of Knockouts | 2 | Application Sector | Commercial | | | | |
| Standard | cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC | Туре | Poke-Thru | | | | |
| Dimensions | | | | | | | |
| Cubic Capacity | 24.5 cu in | | | | | | |
| Listing Agencies / 3rd Party Agencies | | | | | | | |
| cULus ListingNumber | E2961 | cULus Listed | Yes | | | | |

Additional Information

| RoHS Conformant | Yes | | | | | | |
|-----------------------|---------|--|--|-------------------|---|--|--|
| Technical Information | | | | | | | |
| Cable Entry | CONDUIT | | | Number of Outlets | 2 | | |