


Wiremold

RC9 Single-Service Poke-Thru Device Finish Flange and Slide Holder Assembly Part No. RC9CTCGY



Flange available painted in gray (GY), black (BK), ivory (VY), and brushed metal finishes in aluminum (AL) and brass (BS). Aluminum and brass flanges shipped with black cover. Brass flange also available with brass colored cover assembly (AB). Aluminum flange also available with aluminum colored cover assembly (AA). Cover assembly also includes two openings for pass-through capability for one 4-pair Category 5e or Category 6 cable per opening. NOTE: Assembled with scrub water gasket. For use on tile or carpet floors. RC9 Series Poke-Thru Devices require a 3 1/16" [78mm] diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8" minimum.

Features & Benefits

Flange available painted in gray (GY), black (BK), ivory (VY), and brushed metal Aluminum and brass flanges shipped with finishes in aluminum (AL) and brass (BS). black cover

Brass flange also available with brass colored cover assembly (AB)

Aluminum flange also available with aluminum colored cover assembly (AA)

Cover assembly also includes two openings for pass-through capability for one For use on tile or carpet floors 4-pair Category 5e or Category 6 cable per opening

For use on tile or carpet floors

RC9 Series Poke-Thru Devices require a 3 1/16" [78mm] diameter hole

Not designed to work with bare concrete or terrazzo

Floor covering thickness 1/8" minimum

Not designed to work with bare concrete or terrazzo

Specifications

General Info

Product Line	Wiremold	Color	Gray
UPC Number	786564005551	Country Of Origin	Mexico
Construction	Assembled	Application Sector	Commercial, Education, Healthcare, Hospitality
Standard	cULus Listed, NEC	Warranty Type	1-Year from Installation or 2-Years from Day of Sale
Туре	Accessory		

Dimensions

Product Weight US	1.193 lb			
Listing Agencies / 3rd F	Party Agencies			
cULus ListingNumber	E2961	cULus Listed	Yes	
Additional Information				
RoHS Compliant	Yes			