

Tamper-Resistant Heavy-Duty Decorator Hospital Grade Receptacles, Back and Side Wire, 20A, 125V



Features & Benefits

Dual mechanical shutter system to help prevent insertion of foreign objects.

Auto-ground clip assures positive ground.

Easily accessed break-off line-contact connecting tab for fast and easy splitcircuit wiring.

Backed-out tri-drive brass terminal screws for faster installation.

Internal screw-pressure-plate back and side wire capability.

Two back wire holes for additional wiring flexibility.

.032 inch thick brass triple-wipe power contacts.

Two drive screws anchor steel strap to back body and face where abrupt removal torque is greatest.

For covering patents, see www.legrand.us/patents.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Specifications

| General Info | | | | | |
|---------------------------------------|--------------------------------------|-----------------------|------------|--|--|
| Product Line | Pass & Seymour | Color | Gray | | |
| Country Of Origin | Mexico | Number of Receptacles | 2 | | |
| Outlet Type | Commercial, Indoor, Tamper-Resistant | Application Sector | Commercial | | |
| Standard | UL 498 | Туре | Outlet | | |
| Dimensions | | | | | |
| Product Width US | 1.322 in | Product Depth US | 0.78 in | | |
| Product Height US | 2.635 in | | | | |
| Listing Agencies / 3rd Party Agencies | | | | | |
| cULus ListingNumber | 140596 | cULus Listed | Yes | | |

Technical Information

| Is Tamper-Resistant | Yes | Phase | 3 |
|---------------------|-------------|-----------|-------------|
| Number of Wires | 3 | Amperage | 20 A |
| Number of Poles | Double Pole | Wire Size | 14 - 10 AWG |
| Indoor/Outdoor | Indoor | Voltage | 125.0 V |