

Tamper-Resistant Heavy-Duty Decorator Hospital Grade Receptacles, Back and Side Wire, 20A, 125V

## Features & Benefits

Dual mechanical shutter system to help prevent insertion of foreign objects.

Auto-ground clip assures positive ground.

Easily accessed break-off line-contact connecting tab for fast and easy split-circuit wiring.

Backed-out tri-drive brass terminal screws for faster installation.

Internal screw-pressure-plate back and side wire capability.

Two back wire holes for additional wiring flexibility.

.032 inch thick brass triple-wipe power contacts.

Two drive screws anchor steel strap to back body and face where abrupt removal torque is greatest.

For covering patents, see www.legrand.us/patents.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

## **Specifications**

## General Info

General Info				
Product Line	Pass & Seymour	Color	Gray	
UPC Number	785007277487	Country Of Origin	Mexico	
Number of Receptacles	2	Outlet Type	Tamper-Resistant	
Application Sector	Commercial, Hospital Grade	Standard	UL 498, FEDSPEC	
Туре	Outlet			
Dimensions				
Product Width US	1.322 in	Product Depth US	0.78 in	

Product Width US	1.322 in	Product Depth US	0.78 in
Product Height US	2.635 in		

## Listing Agencies / 3rd Party Agencies

cULus ListingNumber 140596 cULus Listed Yes

Technical Information						
Is Tamper-Resistant	Yes	Phase	Three			
Number of Wires	3	Amperage	20 A			
Number of Poles	Double Pole	Wire Size	14 - 10 AWG			

Indoor

Indoor/Outdoor