

Tamper-Resistant Heavy-Duty Decorator Hospital Grade Receptacles, Back and Side Wire, 20A, 125V

Features & Benefits

Dual mechanical shutter system to help prevent insertion of foreign objects.

Auto-ground clip assures positive ground.

Easily accessed break-off line-contact connecting tab for fast and easy split-circuit wiring.

Backed-out tri-drive brass terminal screws for faster installation.

Internal screw-pressure-plate back and side wire capability.

Two back wire holes for additional wiring flexibility.

.032 inch thick brass triple-wipe power contacts.

Two drive screws anchor steel strap to back body and face where abrupt removal torque is greatest.

For covering patents, see www.legrand.us/patents.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Specifications

General Info

Pass & Seymour	Color	White
Matte	UPC Number	785007277456
Mexico	Number of Receptacles	2
Tamper-Resistant	Application Sector	Commercial, Hospital Grade
UL498, cUL CSA, FEDSPEC	Туре	Outlet
1.322 in	Product Depth US	0.78 in
2.635 in		
Party Agencies		
	Tamper-Resistant UL498, cUL CSA, FEDSPEC 1.322 in 2.635 in	Tamper-Resistant Application Sector UL498, cUL CSA, FEDSPEC Type 1.322 in Product Depth US 2.635 in

cULus Listed

Yes

140596

cULus ListingNumber

Technical Information					
Dielectric Strength	Withstands 2000V minimum	Is Tamper-Resistant	Yes		
Temperature Rating	-40° - 60° C	Amperage	20 A		
Number of Poles	Double Pole	Wire Size	14 - 10 AWG		

Indoor/Outdoor

Indoor