



Pass and Seymour  
Tamper-Resistant Isolated Ground Decorator Spec Grade Receptacle, Back and Side Wire, 15A, 125V, Ivory  
Part No. TRIG26262I



Tamper-Resistant Isolated Ground Decorator Spec Grade Duplex Receptacle, Back and Side Wire, 15amp 125volt, Orange. For detailed Tamper-Resistant receptacle information, visit our Tamper-Resistant Receptacles page.

## Features & Benefits

Dual mechanical shutter system to help prevent insertion of foreign objects.

Auto-ground clip assures positive ground.

Easily accessed break-off line-contact connecting tab for fast and easy split-circuit wiring.

Backed-out tri-drive brass terminal screws for faster installation.

Internal screw-pressure-plate back and side wire capability.

Two back wire holes for additional wiring flexibility.

Corrosion-resistant plated steel strap is locked in to face and back body to resist pulling away from the face/body assembly.

.032 inch thick brass triple-wipe power contacts.

Two drive screws anchor steel strap to back body and face where abrupt removal torque is greatest.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

## Specifications

### General Info

|                    |                |                   |                      |
|--------------------|----------------|-------------------|----------------------|
| Product Line       | Pass & Seymour | Color             | Ivory                |
| UPC Number         | 785007012439   | Country Of Origin | Mexico               |
| Application Sector | Commercial     | Standard          | cULus UL498, FEDSPEC |

### Dimensions

|                   |          |                  |         |
|-------------------|----------|------------------|---------|
| Product Width US  | 1.187 in | Product Depth US | 1.25 in |
| Product Height US | 3.625 in |                  |         |

### Listing Agencies / 3rd Party Agencies

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140596 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

---

Technical Information

|                          |                          |                     |             |
|--------------------------|--------------------------|---------------------|-------------|
| Dielectric Strength      | Withstands 2000V minimum | Is Tamper-Resistant | Yes         |
| Connection               | Back and side wire       | Number of Wires     | 3           |
| Temperature Rating       | -40° - 60° C             | Amperage            | 15 A        |
| Number of Poles          | Double Pole              | Wire Size           | 14 - 10 AWG |
| Environmental Conditions | Flammability: UL94 V2    |                     |             |

---