

## Wiremold Plugmold Hard-Wired Multi-Outlet Strip 3 foot long with receptacles 6 inches on center, Ivory

Part No. V20GB306



The Wiremold 2000 Series raceway offers a selection of steel, aluminum, and nonmetallic raceways that provide a versatile solution for many applications. Plugmold sections offer single or alternating circuits, in standard or isolated ground receptacles. The ScuffCoat finish is scratch resistant and protects against nicks and chips while preventing color from fading.

## Features & Benefits

Steel Raceway. Provides superior strength for any dry location installation.

Available in Ivory ScuffCoat or gray baked enamel finish. The durable ScuffCoat provides a durable, scratch-resistant finish while the gray baked enamel compliments the décor or can be painted.

Single-and-dual-gang boxes. Wire devices into the raceway system or protect a Plugmold® strip with a surge or GFCI device.

Single, alternating circuit, and isolated ground receptacles. Meets virtually any job requirement.

Snapicoil harnesses of prewired receptacles in 48' and 50'. Eliminates multiple splicing, speeding up installation on long runs.

Customization available. All products can be modified to accommodate virtually any application.

Compact, low profile appearance. Requires minimal space.

Full range of fittings. Provides a complete wiring solution.

Factory wired Plugmold® sections available in 3', 5', and 6' lengths with 15A receptacles installed in cover. Ideal for short runs requiring additional outlets in electrically busy areas.

Choice of receptacle spacing. Center spacing between receptacles of 6'', 9'', 12'', and 18''.

Snapicoil harnesses offer a choice of receptacle spacing. Center spacing between receptacles of 12", 18" and 30".

This product meets the material restrictions of RoHS.

## **Specifications**

Viremold	Color	
	Cotton	lvory
86776093162	Country Of Origin	United States
	Application Sector	Residential/Commercial
ULus Listed Multioutlet Assembly: File 15191 Guide PVGT/PVGT7	Туре	Plugmold
6.0 in	Product Weight US	1.79 lb
9.6 cu in	Product Depth US	0.88 in
(	JLus Listed Multioutlet Assembly: File 15191 Guide PVGT/PVGT7 5.0 in	Application Sector  ULus Listed Multioutlet Assembly: File 15191 Guide PVGT/PVGT7  5.0 in Product Weight US

Listing Agencies / 3rd Party  cULus ListingNumber E18  Buy American Act Complian	y Agencies 5191	cULus Listed	Yes
cULus ListingNumber E18 Buy American Act Complian	5191	cULus Listed	Yes
Buy American Act Complian		cULus Listed	Yes
	nce		
NAFTA Yes	s		
Additional Information			
RoHS Conformant Yes	S	Product Environmental Profile	Yes
Technical Information			
Frequency Rating 60	Hz	Amperage	15 A
Enclosure Type Ste	eel	Voltage	125.0 V
Environmental Conditions Dry	ry interior locations		