

Wiremold

Wiremold 20GB306TR Tamper Resistant Plugmold Multioutlet System with Self Testing GFCI in White

Part No. WH20GB306TRGFI6

The Wiremold 2000 Series raceway offers a selection of steel, aluminum, and nonmetallic raceways that provide a versatile solution for many applications. Plugmold sections offer single or alternating circuits, in standard or isolated ground receptacles. The ScuffCoat finish is scratch resistant and protects against nicks and chips while preventing color from fading.



Features & Benefits

The Wiremold 2000 Series raceway offers a selection of steel, aluminum, and nonmetallic raceways that provide a versatile solution for many applications. Plugmold sections offer single or alternating circuits, in standard or isolated ground receptacles. The ScuffCoat finish is scratch resistant and protects against nicks and chips while preventing color from fading.

Specifications

| | General Info | | | | |
|--|---|---|--|--|--|
| Wiremold | Color | White | | | |
| 786776188127 | Country Of Origin | United States | | | |
| 5 | Application Sector | Residential/Commercial | | | |
| cULus Listed Multioutlet Assembly: File E15191 Guide PVGT/PVGT7 | Туре | Plugmold | | | |
| Dimensions | | | | | |
| 36.0 in | Product Weight US | 1.79 lb | | | |
| 44.01 cu in | Product Depth US | 0.75 in | | | |
| 1.63 in | | | | | |
| Listing Agencies / 3rd Party Agencies | | | | | |
| E15191 | cULus Listed | Yes | | | |
| Buy American Act Compliance | | | | | |
| Yes | | | | | |
| _ | 786776188127 5 cULus Listed Multioutlet Assembly: File E15191 Guide PVGT/PVGT7 36.0 in 44.01 cu in 1.63 in Party Agencies E15191 | 786776188127 Country Of Origin Application Sector CULus Listed Multioutlet Assembly: File E15191 Guide PVGT/PVGT7 Type 36.0 in Product Weight US 44.01 cu in Party Agencies E15191 cULus Listed | | | |

| RoHS Conformant | Yes | Product Environmental Profile | Yes | |
|-----------------------|-------|-------------------------------|---------|--|
| Technical Information | | | | |
| Frequency Rating | 60 Hz | Amperage | 15 A | |
| Enclosure Type | Steel | Voltage | 125.0 V | |