

## Wiremold GFCI PLUGMOLD 5FT WHITE 9 OUTLETS AND SELF TEST GFCI MODULE

Part No. WH20GB506TRGFI6



Plugmold® Multioutlet Systems are available in a wide variety of lengths and fittings and in a variety of finishes to provide versatile solutions for many applications. Plugmold options include single or alternating circuits, standard or isolated ground receptacles, GFCI protection, tamper-resistant protection, USB charging, Snapicoil® harnesses of prewired receptacles, and cord-ended units. Plugmold® Multioutlet Systems are available in black or ivory ScuffCoat™ finish, painted white or gray enamel steel, stylish stainless steel, anodized aluminum and durable textured ivory nonmetallic. The painted steel product works with many types of decor and is paintable to integrate with most color schemes. Durable stainless steel and anodized aluminum Plugmold products are corrosion-resistant, making them ideal for labs.

## Features & Benefits

Compact, low profile appearance. Enhanced aesthetics and ideal for installations within minimal spaces.

## **Specifications**

| Product Line       | Wiremold      | UPC Number            | 786776188134  |
|--------------------|---------------|-----------------------|---|
| Country Of Origin  | United States | Number of Receptacles | 1   |
| Application Sector | Residential   | Standard              | cULus Listed Base & Blank<br>Cover: File e4376 Guide RJBT,<br>Multi-Outlet Assemblies: File<br>E15191 Guide PVGT, Fittings:<br>File E41751 Guide RJPR, Base &<br>Blank Cover: Meets Article 386<br>of NEC, Plugmold Strips: Meets<br>Article 380 of NEC |
| Гуре               | Plugmold      |                       |   |
| Dimensions         |               |                       |   |
| Product Width US   | 1.3 in        | Product Weight US     | 3.17 lb   |
| Product Depth US   | 0.75 in       | Product Length US     | 1.3 in  |

| cULus ListingNumber    | E15191  | cULus Listed   | Yes   |  |
|------------------------|---------|----------------|-------|--|
| Trade Programs         |         |                |       |  |
| USMCA                  | Yes     |                |       |  |
| Additional Information |         |                |       |  |
| RoHS Compliant         | Yes     |                |       |  |
| Technical Information  |         |                |       |  |
| Amperage               | 20 A    | Enclosure Type | Steel |  |
| Voltage                | 125.0 V |                |       |  |