

Pass and Seymour 250V Weather-Resistant Tamper-Resistant Heavy Duty Spec Grade 20A Single Receptacle with Back and Side Wire Connections, White Part No. WR5871TRW



Weather-Resistant Tamper-Resistant Heavy Duty Spec Grade Single Receptacle, Back and Side Wire, 20A, 250V

Features & Benefits

| locked in to face and back body to resist pul | One-piece brass, triple-wipe power contacts for lasting retention | | | | |
|--|--|--|--|--|--|
| Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring | | Impact-resistant nylon face and thermoplastic back body | | | |
| Internal screw-pressure-plate back wire capable of accepting 14 to 10 AWG solid or stranded copper or copper-clad wire | | r Terminal compartments isolated from each other for positive conductor containment | | | |
| VS | Auto-ground clip assures positive ground | | | | |
| WR marking on face as required by UL Standard | | | | | |
| Specifications | | | | | |
| | | | | | |
| Pass & Seymour | Color | White | | | |
| Glossy | UPC Number | 785007378313 | | | |
| Mexico | Receptacle Ty | e Single | | | |
| | t connecting tab for fast, easy split-circuit wi ire capable of accepting 14 to 10 AWG solid o vs .Standard Pass & Seymour Glossy | re capable of accepting 14 to 10 AWG solid or stranded copper vs . Standard Pass & Seymour Color Glossy UPC Number | | | |

 Number of Receptacles
 1
 Outlet Type
 Weather-Resistant

 Application Sector
 Commercial
 Standard
 UL, CSA, FEDSPEC

 Warranty Type
 1-Year Limited Warranty
 Type
 Outlet, Tamper-Resistant, Weather-Resistant

Listing Agencies / 3rd Party Agencies

| CSA Listed | Yes | cULus ListingNumber | E140596 |
|-----------------------|-----------------------|--------------------------|-----------------------|
| cULus Listed | Yes | CSA File Number | C22.2 No. 42 |
| Technical Information | | | |
| Seismic Tested | No | Is Tamper-Resistant | Yes |
| Connection | Back and/or Side Wire | Amperage | 20 A |
| Wire Size | 14 - 10 AWG | Is Weather Resistant | Yes |
| Indoor/Outdoor | Outdoor | Mounting Type | Box |
| Connection Type | Wired | Environmental Conditions | Flammability: UL94 V2 |
| | | | |