


Wiremold 5' Alternating USB Aluminum Plugmold® Multioutlet System Part No. AL20GB509TRUSBA



Available in 5' (1.5m) length with 9" spacing. 15A tamper-resistant receptacles. 3-wire, #12 USB Plugmold THHN (1 hot, 1 neutral and insulated ground conductor). .040" (1.0 mm) aluminum housing. Packed two per carton. Each unit supplied with one (1) Coupling and two (2) Blank End Fittings. USB is 2.4 Amps (shared between two ports) 5VDC. Please note the charging load on one module will not affect the charging performance of the other USB modules in the product.

Features & Benefits

or other mobile devices at the same time.

USB charging. Dual-port charging modules share 2.4 amps Compact design. Low-profile design installs in tight locations of charging capacity and can charge multiple phones, tablets while offering multiple power and USB charging connections. Receptacle spacing accommodates bulky AC adapters.

Tamper-resistant receptacles. Prevents the insertion of foreign objects into receptacles reducing the risk of shocks or electrocution. Meets 2014 NEC section 406 requirements.

Specifications

General Info			
Product Line	Wiremold	UPC Number	786776184426
Country Of Origin	United States	Number of Receptacles	6
Application Sector	Commercial	Standard	cULus Listed Multioutlet Assembly: File E15191 Guide PVGT
Туре	Plugmold		
Dimensions			
Product Width US	1.42 in	Product Depth US	1.13 in
Product Length US	1.42 in		
Listing Agencies / 3rd F	Party Agencies		
cULus ListingNumber	E15191	cULus Listed	Yes

Buy American Act Compliance						
NAFTA	Yes					
Additional Information						
RoHS Conformant	Yes	Product Environmental Profile	Yes			
Technical Information						
Frequency Rating	60 Hz	Amperage	20 A			
Enclosure Type	Aluminum	Voltage	125.0 V			
Environmental Conditions	Dry interior locations					