



Pass and Seymour Non-Fusible Mechanical Interlock Part No. PS460MIR9W

Triple-Pole, 4-Wire, Non-Fusible Mechanical Interlock Receptacle. 60A, 3, 240V.

Features & Benefits

| Top or Bottom feed. | Unit shipped with no holes drilled: a top and bottom feed spot drill is provided for locating hole saw or knockout. |
|---|---|
| End user decides at installation whether top or bottom feed is appropriate. | No closure plug kits required. |
| Specifications | |

General Info

| Product Line | Pass & Seymour | Color | Gray | | | |
|---------------------------------------|----------------|--------------------|------------|--|--|--|
| Country Of Origin | United States | Application Sector | Commercial | | | |
| Standard | UL Listed | | | | | |
| Dimensions | | | | | | |
| Product Width US | 6.88 in | Product Depth US | 9.0 in | | | |
| Product Height US | 9.0 in | | | | | |
| Listing Agencies / 3rd Party Agencies | | | | | | |
| cULus ListingNumber | 31169 | cULus Listed | Yes | | | |

Technical Information

| Phase | Three | Number of Wires | 4 |
|-----------|-------|-----------------|---------|
| Amperage | 60 A | Number of Poles | 3-Way |
| Wire Size | 2 AWG | Voltage | 250.0 V |